Safety Data Sheet



Revision Number: 004.1

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type: Lubric Restriction of Use: None Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

BONDERITE L-FM MP 404 FORMING LUBRICANT ACHESON known as Geroform MP 404 F184 WENS Lubricant None identified

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

1737477

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

 HAZARD CLASS
 HAZARD CATEGORY

 None
 None

PICTOGRAM(S)

None

Precautionary Statements

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	50 - 60

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.	
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.	
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.	
Ingestion:	Get immediate medical attention. Do not induce vomiting.	
Symptoms:	See Section 11.	
Notes to physician:	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.	
5. FIRE FIGHTING MEASURES		

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	This product is combustible at high temperatures. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection. Remove all sources of ignition.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not take internally. For industrial use only. Launder work clothes frequently.
Storage:	For safe storage, store at or above 4.4 °C (39.9 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction. 5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Engineering controls:		local and general exhau buildup of any vapors o		
Respiratory protection:	vapors, Respirat health a respirat protecti provisio mainter implem approve For con limits, a cartridg consult	ation is not sufficient to e appropriate NIOSH/MSI ators should be selected and safety professional for or standard (29 CFR 19 on (Z88.2-1992). A writte ons for medical certification nance, inspection, cleani ented. If concentrations ented disposable dust/mist in centrations above the TI NIOSH approved half-fa- les may be used. For con- the NIOSH respirator de 88.2-1992.	HA respiratory protection by and used under the collowing requirements fo 10.134) and ANSI's stan en respiratory protection on, training, fit testing, ex ng, and convenient, san are below the TLV and/c respirator may be used f LV and/or PEL but less t accepiece respirator equip ncentrations greater thar	n must be provided. direction of a trained bund in OSHA's dard for respiratory program, including xposure assessments, itary storage must be or PEL, a NIOSH or personal comfort. han 10 times these pped with dust-mist n 10 times these limits,
Eye/face protection:	Wear cl	hemical goggles; face sh	ield (if splashing is poss	sible).
Skin protection:	include	cal resistant, impermeabl : Nitrile gloves. Neopren ity for prolonged contact. nended.	e gloves. Gloves should	be tested to determine

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Specific gravity:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Decomposition temperature:
peraturer

Liquid Amber Petroleum Not available. Not applicable Not determined > 100 °C (> 212°F)calculated Not determined 0.91 - 0.94 at 16 °C (60.8 °F) Not determined 137.8 °C (280.04 °F) Cleveland open cup Not available. Not available. Not determined Not applicable Not available. Negligible Not determined Not applicable Not available. Not available.

IDH number: 1737477

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.	
Hazardous reactions:	Will not occur.	
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.	
Incompatible materials:	Strong oxidizing agents.	
Reactivity:	Not available.	
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.	
11. TOXICOLOGICAL INFORMATION		

Relevant routes of exposure. Skin, innalation, Eyes	Relevant routes of exp	oosure: SI	kin, Inhalation, E	ves
---	------------------------	------------	--------------------	-----

Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
	Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
Skin contact:	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.
Eye contact:	This product may cause irritation to the eyes.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispo

Hazardous waste number:

Dispose of according to Federal, State and local governmental regulations.

Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (Proper shipping name: Hazard class or division: Identification number: Packing group:	49 CFR) Not regulated None None None
International Air Transportation (ICAO/IATA)	1
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health None above reporting de minimis.
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
Canada Regulatory Information	

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

Issue date: 12/07/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.