# **Safety Data Sheet**



Revision Number: 002.0 Issue date: 03/10/2022

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-MR CR 26 METAL IDH n

**REMOVAL known as MULTAN CR 26** 

Product type/use: Lubricant Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 910480

Region: United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGÉNCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

# EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY	
None	None	

	PICTOGRAM(S)
Ī	None

#### **Precautionary Statements**

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr)	64742-54-7	60 - 80

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

IDH number: 910480 Product name: BONDERITE L-MR CR 26 METAL REMOVAL known as MULTAN CR 26

Page 1 of 5

Ingestion: Get medical attention. DO NOT induce vomiting unless directed to do so by

medical personnel.

Symptoms: See Section 11.

Notes to physician: This material, if aspirated into the lungs, may cause chemical pneumonitis;

treat the affected person appropriately.

## FIRE FIGHTING MEASURES

**Extinguishing media:** Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus. Wear full protective clothing.

This product is combustible at high temperatures. Unusual fire or explosion hazards:

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

## **ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate personal

protective equipment. Remove all sources of ignition.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

## HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Wash thoroughly after handling. Do not take internally. For

industrial use only. Launder work clothes frequently.

For safe storage, store between 40 °F (4.4 °C) and 100 °F (37.8 °C) Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty

containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## **EXPOSURE CONTROLS / PERSONAL PROTECTION**

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr)	None	5 mg/m3 PEL Mist.	None	None

**Engineering controls:** Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

IDH number: 910480

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:Medium amberOdor:PetroleumOdor threshold:Not available.pH:Not applicableVapor pressure:1 mm hg calculated

Boiling point/range: > 210 °C (> 410°F)calculated

Melting point/ range: Not determined

**Specific gravity:** 0.86 - 0.88 at 21.1 °C (69.98 °F)

Vapor density: Not determined

Flash point: > 204.4 °C (> 399.92 °F) Cleveland open cup

Flammable/Explosive limits - lower: Not determined Flammable/Explosive limits - upper: Not determined Autoignition temperature: Not determined Flammability: Not applicable **Evaporation rate:** Not applicable Solubility in water: Negligible Partition coefficient (n-octanol/water): Not determined **VOC** content: Not applicable Viscosity: Not available. **Decomposition temperature:** Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition Upon decor

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

**Incompatible materials:** This product may react with strong oxidizing agents.

Reactivity: Not available.

**Conditions to avoid:** Keep away from heat, ignition sources and incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation:Inhalation of vapors or mists of the product may be irritating to the respiratory system.Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.Skin contact:Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

**Eye contact:** This product may cause irritation to the eyes.

Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this

product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr)	Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 9.6 mg/l Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.53 mg/l	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy paraffinic (not cmr)	No	No	No

IDH number: 910480 Product name: BONDERITE L-MR CR 26 METAL REMOVAL known as MULTAN CR 26 Page 3 of 5

# 12. ECOLOGICAL INFORMATION

**Ecological information:**No data available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

TSCA 12 (b) Export Notification: Control Act (TSCA) inventory.

None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: John DiCerbo, Sr. Regulatory Affairs Specialist

**Issue date:** 03/10/2022

IDH number: 910480 Product name: BONDERITE L-MR CR 26 METAL REMOVAL known as MULTAN CR 26

Page 4 of 5

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.