

Revision Number: 004.0 Issue date: 07/18/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-FG F-54 FORGING IDH number:

LUBRICANT ACHESON known as F-

54

Product type: Lubricant

Restriction of Use: None identified

Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1225015

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 1225015 Product name: BONDERITE L-FG F-54 FORGING LUBRICANT ACHESON known as F-54

Page 1 of 5

Hazardous Component(s)	CAS Number	Percentage*
Sodium salt	Proprietary	10 - 20
Triazine compound	Proprietary	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get medical attention. DO NOT induce vomiting unless directed to do so by

medical personnel.

Symptoms: See Section 11.

IDH number: 1225015

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Provide adequate ventilation. For industrial

use only.

Storage: For safe storage, store between 5 °C (41°F) and 32 °C (89.6 °F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Sodium salt	None	None	None	None
Triazine compound	None	None	None	None

Ventilation should effectively remove and prevent buildup of any **Engineering controls:**

vapor/mist/fume/dust generated from the handling of this product.

Respiratory protection: When dusts or thermal processing fumes are generated and ventilation is not

sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Water white Color: Odor: Mild

Odor threshold: Not available. pH: 8.5 - 9.5 Vapor pressure: Not determined

Boiling point/range: 100 °C (212°F)calculated

Melting point/ range: < 0 °C (< 32°F) Specific gravity: 1.08 - 1.1 Vapor density: Not determined Flash point: Not applicable Flammable/Explosive limits - lower: Not applicable Flammable/Explosive limits - upper: Not applicable Autoignition temperature: Not applicable Flammability: Not applicable **Evaporation rate:** 1 (Water = 1)Solubility in water: Complete Partition coefficient (n-octanol/water): Not determined **VOC** content: 0 %; 0 g/l (calculated) Viscosity: 2,200 - 4,000 cp

Decomposition temperature:

IDH number: 1225015 Product name: BONDERITE L-FG F-54 FORGING LUBRICANT ACHESON known as F-54

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Incompatible materials: This product may react with strong acids or oxidizing agents. Halogenated compounds. Avoid

contact with iron, aluminum, zinc, copper and strong bases.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of mist or spray may cause irritation of the respiratory tract and nasal passages.

Skin contact: This product may cause irritation to the skin.

Eye contact: Liquid or vapor can cause moderate to severe irritation.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Sodium salt	None	Irritant, Respiratory, Nervous System, Gastrointestinal, Liver, Kidney
Triazine compound	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Sodium salt	No	No	No
Triazine compound	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 1225015

Product name: BONDERITE L-FG F-54 FORGING LUBRICANT ACHESON known as F-54

Page 4 of 5

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health None above reporting de minimis. None above reporting de minimis.

None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present. No California

Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 1225015

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format. 9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 07/18/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: BONDERITE L-FG F-54 FORGING LUBRICANT ACHESON known as F-54

Page 5 of 5