Safety Data Sheet

M520 ZIP Slip® Silicone Anti-Stick Grease



THE MOLDER'S EDGE

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc., product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated Product Name: ZIP Slip® Silicone Anti-Stick Grease

1070 Robert Fulton Hwy.

Quarryville, PA 17566

Product Code: M520
Product Use: Lubricant

1-800-227-5538 24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification Not classified as hazardous.

3. COMPOSITION/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 Percent

 NJ Trade Secret Registry
 #80100382-5036P
 80 - 100

 Amorphous Silica
 112945-52-5
 1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 1 Physical: 0 Personal See Section 8 Protective

Equipment:

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if

symptoms persist. Seek medical attention if symptoms persist. Wash clothing before reuse.

Ingestion: Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by

mouth if victim is rapidly losing consciousness or is unconscious or convulsing.

Inhalation: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. Remove affected person to fresh

air. No first aid should be needed.

NOTES TO PHYSICIAN:

No additional first aid information available.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: Hazardous decomposition products may be formed (see Sec.10).

Fire Fighting Instructions: Use water spray, foam, dry chemical, or CO2. Water is generally not effective and may spread fire; however,

water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

Equipme

^{*} See www.paint.org/hmis or call the NPCA at 1 (202) 462-6272 for more information on this current rating system.

7. HANDLING AND STORAGE

Normal precautions common to safe manufacturing practice should be followed in handling and storage. Handling:

Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Storage:

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the MSDS (from Engineering Controls:

known, suspected or apparent adverse effects).

The use of safety glasses with side shields is recommended if there is any probability of liquid contact with the eyes. Eye Protection:

The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with Skin Protection:

Respiratory Protection: None required for well ventilated situations.

COMPONENT CAS# ACGIH TLV OSHA PEL OTHER NJ Trade Secret Registry #80100382-5036P Not established Not established Not established

Amorphous Silica 112945-52-5 3 mg/m3 TWA, 6.0 mg/m3 Not established

Respirable dust

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Lower Flammability Limit (%): Not applicable Paste Appearance: Opaque Upper Flammability Limit (%): Not applicable Odor: Characteristic 0.00 Vapor Pressure (PSIG @ 70°F): Odor Threshold: None Vapor Density [air = 1]: 1.11 Not applicable 1.02 Relative Density (H2O=1): pH:

Melting/Freezing Point (°F): No data available Solubility in Water: Not determined No data available Partial Coefficient: n-Boiling Point (°F): No data available

octanol/water:

Autoignition Temperature (°F): Flash Point (°F PMCC): 610 Not applicable **Evaporation Rate:** 0.5-2 (n-Butyl acetate = 1) Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available

Percent VOCs (%): 0.1-0.99

10. STABILITY AND REACTION

Chemical Stability: Stable. Conditions to Avoid: None known.

Burning can produce the following combustion products: Carbon dioxide and carbon monoxide. When heated to Decomposition Products:

temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant

and a potential cancer hazard at concentrations greater than 0.75 ppm. Oxides of siloxanes.

11. TOXICOLOGICAL INFORMATION

No data available. Reproductive & Developmental

Toxicity:

Ingredient CAS# **Toxicological Data**

Dermal LD50 Rabbit > 2000 mg/kg NJ Trade Secret Registry #80100382-5036P Oral LD50 Rat > 15400 mg/kg Dermal LD50 Rabbit >= 2000 mg/kg 112945-52-5 Amorphous Silica

Oral LD50 Rat >= 5000 mg/kg

12. ECOLOGICAL INFORMATION

Ecological Toxicity: Based on analogy to similar materials, this product is expected to exhibit low toxicity to aquatic organisms.

Mobility: No data available

Degradability: This produt degrades in soil abiotically to form smaller molecules. These in turn are either biodegraded in soil or

volatilized into the air where they are broken down in the presence of sunlight.

Ingredient CAS# **Toxicological Data**

NJ Trade Secret Registry #80100382-5036P 48HR EC50 Daphnia > 200 mg/L

Amorphous Silica 112945-52-5 Aquatic LC50 (96h) MINNOW > 10000 mg/L

13. DISPOSAL CONSIDERATIONS

Dispose according to Federal, State and local regulations. Disposal:

14. TRANSPORTATION INFORMATION

UN Number Proper Shipping name Hazard Class Packing Group Agency

DOT Not regulated by agency IATA Not regulated by agency **IMDG** Not regulated by agency

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT CAS# % BY WEIGHT Regulatory Body

No components listed in this section. SARA Section 313

Warning: This product may contain chemicals known to the State of California to cause cancer. See list below.

No components listed in this section. Prop65 Cancer

Warning: This product may contain chemicals known to the State of California to cause birth defects. See list below.

No components listed in this section. Prop65 Birth Defects

All components of this product are listed on the TSCA inventory.

16. OTHER INFORMATION

Other Information: MSDS Prepared by L. Dean Swartz, MSDS Coordinator

06/01/15 Version Date:

This information contained in this MSDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.