

BONDERITE S-OT 44 ACHESON TIRE MOUNTING LUBRICANT

Issued 6/22/2017

1. Introduction:

BONDERITE S-OT 44 ACHESON is an odorless, very slightly viscous, liquid material specifically formulated to possess lubrication properties. It is a water-based material which is ready to use out of the drum. BONDERITE S-OT 44 ACHESON residues can be easily rinsed off with tap water, but rinsing is not necessary.

It is especially suited for use as a lubricant in any manual or automatic tire mounting operation. It will not attack painted or unpainted surfaces.

2. Operating Summary:

Chemical and Use:

BONDERITE S-OT 44 ACHESON is used directly as supplied.

Operation:

BONDERITE S-OT 44 ACHESON can be applied manually by brushing or swabbing. It can also be used as supplied in automatic tire mounting equipment and is suited for production line work.

3. Storage Requirements:

BONDERITE S-OT 44 ACHESON will freeze at temperatures below 32° Fahrenheit, but it will return to a uniform liquid upon thawing with no separations or cloudiness.

4. Equipment:

The equipment used for dispensing BONDERITE S-OT 44 ACHESON may be constructed of mild steel.

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | www.henkelna.com/

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. © denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

