SP Ashland always solving ™	Page: 1
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : STYLE FUSION COMPLEX 3

polymer

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Personal care

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	,
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America (USA)	
614-790-3333	Product Information
	614-790-3333
EHSProductSafety@ashland.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
CATIONIC GUAR GUM,	65497-29-2		3.5011
MODIFIED		Eye Irrit. 2A; H319	

Ashland always solving	Page: 2
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Ashland always solving	Page: 3
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

Specific extinguishing

methods

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Components	CAS-No.
CATIONIC GUAR GUM,	65497-29-2
MODIFIED	

Engineering measures : General room ventilation should be adequate for normal

SP Ashland always solving The	Page: 4
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection No personal respiratory protective equipment normally

required.

Not required under normal conditions of use. Wear splash-Eye protection

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

General industrial hygiene practice. Hygiene measures

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

: Microcapsules in Liquid Appearance

Physical state : liquid

Colour white

Odour characteristic

Odour Threshold : No data available

: 6 - 6.5 рΗ

: No data available Melting point/freezing point

Boiling point/boiling range : 203 - 221 °F / 95 - 105 °C

Flash point > 120 °C

Evaporation rate No data available

Flammability (solid, gas) No data available

Ashland always solving	Page: 5
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 1.0 - 1.1 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 12,000 - 22,000 cps

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

UV light.

Exposure to sunlight.

Incompatible materials : Acids

Oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

Ashland always solving	Page: 6
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:

CATIONIC GUAR GUM, MODIFIED:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

CATIONIC GUAR GUM, MODIFIED:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

Ashland always solving	Page: 7
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

CATIONIC GUAR GUM, MODIFIED:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 54 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : NOEC (Blue-green algae (Anabaena flos-aquae)): > 100 mg/l

Exposure time: 72 h

Test Type: Growth inhibition Method: OECD Test Guideline 201

GLP: yes

Persistence and degradability

Components:

CATIONIC GUAR GUM, MODIFIED:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Ashland always solving	Page: 8
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:
No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGIII ATION

REGULATION						
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE	
		CLASS	HAZARDS	GROUP	POLLUTANT /	
					LTD. QTY.	

U.S. DOT - ROAD

0.0.20.
Not dangerous goods

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not (dangerous	goods

PAshland always solving	Page: 9
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

TDG_ROAD_C	
	Not dangerous goods
TDG_RAIL_C	
	Not dangerous goods
TDG_INWT_C	
	Not dangerous goods
INTERNATIONA	L MARITIME DANGEROUS GOODS
	Not dangerous goods
	- The dain governo governo
INTERNATIONA	L AIR TRANSPORT ASSOCIATION - CARGO
INTERNATIONA	
	Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX DG

- 5	
	Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

OLNOLA Reportable equality				
Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
SODIUM HYDROXIDE	1310-73-2	1000	*	

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

Ashland always solving	Page: 10
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

WATER 7732-18-5

CATIONIC GUAR GUM, MODIFIED 65497-29-2

New Jersey Right To Know

WATER 7732-18-5

CATIONIC GUAR GUM, MODIFIED 65497-29-2

HASE COPOLYMER Not Assigned

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Ashland always solving	Page: 11
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 02/16/2017



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet Ashland internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

Ashland always solving	Page: 12
SAFETY DATA SHEET	Revision Date: 02/16/2017
	Print Date: 5/24/2017
	SDS Number: 000000271757
STYLE FUSION COMPLEX 3 polymer	Version: 1.2
885777	

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System