

# **Safety Data Sheet**

## Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	19-5021-1	Version Number:	17.01
Issue Date:	09/06/16	Supercedes Date:	02/05/15

# **SECTION 1: Identification**

## 1.1. Product identifier

3М<sup>тм</sup> Novec<sup>тм</sup> 7300 Engineered Fluid

Product Identification Numbers

98-0212-3243-8, 98-0212-3244-6, 98-0212-3245-3, 98-0212-3384-0

## 1.2. Recommended use and restrictions on use

### Recommended use

For industrial use only. Not intended for use as a medical device or drug.

### **Restrictions on use**

Novec<sup>TM</sup> Engineered Fluids are used in a wide variety of applications, including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

# **1.3. Supplier's details**

MANUFACTURER:	3M
<b>DIVISION:</b>	<b>Electronics Materials Solutions Division</b>
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

**1.4. Emergency telephone number** 1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

# 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **2.2. Label elements Signal word** Not applicable.

**Symbols** Not applicable.

**Pictograms** Not applicable.

2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-	132182-92-4	99 - 100
(trifluoromethyl)-		

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

# Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

# Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

# If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# **4.3.** Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

# 5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

# **5.3.** Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective

clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections.

## **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

# 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid skin contact with hot material. For industrial or professional use only. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

# 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Pentane, 1,1,1,2,2,3,4,5,5,5-	132182-92-	Manufacturer	TWA:100 ppm	
decafluoro-3-methoxy-4-	4	determined		
(trifluoromethyl)-				

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### **8.2.1. Engineering controls**

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is

not adequate, use respiratory protection equipment.

# 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

### **Skin/hand protection**

No chemical protective gloves are required.

## **Respiratory protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Liquid
Odor, Color, Grade:	Clear, colorless liquid. Faint odor.
Odor threshold	No Data Available
pH	Not Applicable
Melting point	-38 °C
Boiling Point	208 °F
Flash Point	No flash point
Evaporation rate	0.07 g/cm2-hr
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	None detected
Flammable Limits(UEL)	None detected
Vapor Pressure	0.81 psia [@ 68 °F]
Vapor Density	0.014 g/cm3 [Details: @ 25 C]
Density	1.6 g/ml
Specific Gravity	1.6 [ <i>Ref Std:</i> WATER=1]
Solubility In Water	0.295 ppm [@ 20 °C]
Solubility- non-water	0.067 Slight (less than 10%) [Details: Solubility of water in
	Novec 7300 (ppm)]
Partition coefficient: n-octanol/ water	4.3 [Details: (log Kow)]
Autoignition temperature	408 °C [Details: per ASTM E-659 method]
Decomposition temperature	> 200 °C [Details: (anhydrous conditions)]
Viscosity	< 5 centipoise [@ 25 °C]
Molecular weight	No Data Available
Volatile Organic Compounds	Not Applicable
Percent volatile	100 %
VOC Less H2O & Exempt Solvents	Not Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

## 10.2. Chemical stability

Stable.

# 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

# **10.4. Conditions to avoid** None known.

# **10.5. Incompatible materials** Strong acids Strong bases Strong oxidizing agents

10.6. Hazardous decomposition products	
Substance	<b>Condition</b>
Carbon monoxide	At Elevated Temperatures - extreme conditions of
	heat
Carbon dioxide	At Elevated Temperatures - extreme conditions of
	heat
Hydrogen Fluoride	At Elevated Temperatures - extreme conditions of
	heat
Toxic Vapor, Gas, Particulate	At Elevated Temperatures - extreme conditions of
	heat

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects** 

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

# Inhalation:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

# Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

# Eye Contact:

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

May be harmful if swallowed.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4- (trifluoromethyl)-	Dermal	Rat	LD50 > 2,000 mg/kg
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4- (trifluoromethyl)-	Inhalation- Vapor (4 hours)	Rat	LC50 > 430 mg/l
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4- (trifluoromethyl)-	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Rabbit	No significant irritation

## **Serious Eye Damage/Irritation**

Name	Species	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Rabbit	No significant irritation

### **Skin Sensitization**

Name	Species	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Mouse	Not sensitizing

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	In Vitro	Not mutagenic

### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Reproductive Toxicity**

### **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3- methoxy-4-(trifluoromethyl)-	Inhalation	Not toxic to reproduction and/or development		NOEL 10,000 ppm	
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3- methoxy-4-(trifluoromethyl)-	Ingestion	Some positive female reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days

# Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Pentane, 1,1,1,2,2,3,4,5,5,5- decafluoro-3-methoxy-4- (trifluoromethyl)-	Inhalation	hematopoietic system   liver   kidney and/or bladder   respiratory system	All data are negative	Rat	NOAEL 143 mg/l	5 days
Pentane, 1,1,1,2,2,3,4,5,5,5- decafluoro-3-methoxy-4- (trifluoromethyl)-	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	28 days
Pentane, 1,1,1,2,2,3,4,5,5,5- decafluoro-3-methoxy-4- (trifluoromethyl)-	Ingestion	endocrine system   bone, teeth, nails, and/or hair   hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Pentane, 1,1,1,2,2,3,4,5,5,5- decafluoro-3-methoxy-4- (trifluoromethyl)-	Ingestion	heart   immune system   nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days

### Specific Target Organ Toxicity - repeated exposure

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

<u>Test Organism</u>	Test Type	<b>Result</b>
Ricefish, Oryzias latipes	96 hours Lethal Concentration 50%	>100 mg/l
Water flea Daphnid, Daphnia ambigua	48 hours Effect Concentration 50%	>100 mg/l
Green algae, Pseudokirchneriella subcapitata	72 hours Effect Growth Rate Conc 50%	>100 mg/l

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials.

Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical

substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated &

disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

# **SECTION 15: Regulatory information**

## **15.1. US Federal Regulations**

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	C.A.S. No	<b>Regulation</b>	<u>Status</u>
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-	132182-92-4	Toxic Substances Control Act (TSCA) 5	Applicable
methoxy-4-(trifluoromethyl)-		SNUR or Consent Order Chemicals	

# This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

Ingredient (Category if applicable)	<u>C.A.S. No</u>	<u>Reference</u>
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3- methoxy-4-(trifluoromethyl)-	132182-92-4	40CFR721.10061

### **15.2. State Regulations**

Contact 3M for more information.

### **15.3.** Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

## **15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

## NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

## **HMIS Hazard Classification Health:** 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	19-5021-1	Version Number:	17.01
Issue Date:	09/06/16	Supercedes Date:	02/05/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

# 3M USA SDSs are available at www.3M.com