

SAFETY DATA SHEET

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name ELVACITE® ACRYLIC RESIN - POLY(MMA/nBMA/MAA) BASED

Product Description Polymer based on Methyl methacrylate, n-Butyl methacrylate and Methacrylic acid.

This data sheet covers the following grades: ELVACITE® 2013, 2013H, 2016, 2550, 2614,

2614T, 2697, 2823, 2934, 2971, 2971C, 4111, 4144, 4149

CAS No. 28262-63-7

Identified use(s)

Manufacture of inks, paints and varnishes.

Coatings.

Uses advised against None known.

Manufacturer Lucite International, Inc., 7275 Goodlett Farms Parkway, Cordova, TN 38016-4909

Phone: 1-800-4-LUCITE msdsinfo@lucite.com

Emergency Phone No. 1-800-424-9300 (Transport Emergency)

1-877-886-2143 (Medical Emergency)

2. HAZARDS IDENTIFICATION

Hazard classification Combustible dust

Label elements

Signal word Warning

Hazard statement(s) May form combustible dust concentrations in air.

Other hazards Low toxicity under normal conditions of handling and use.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical identity of the substance Poly(Methyl methacrylate/n-Butyl methacrylate/Methacrylic acid)

CAS No. 28262-63-7

4. FIRST AID MEASURES

Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention.

Molten material can cause severe burns. Do NOT try to peel molten polymer from the skin.

Cool rapidly with water.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Obtain medical attention if ill

effects occur.

Most important symptoms and effects, both acute and delayed

Not applicable.

Indication of any immediate medical attention and special treatment needed

None necessary.

Revision: GHS4

ELVACITE® ACRYLIC RESIN - POLY(MMA/nBMA/MAA) BASED

Date: 13 -July- 2016

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Unsuitable Extinguishing Media Special hazards arising from the substance

or mixture

Special protective equipment and precautions for fire fighters

Water spray, foam, dry powder or CO₂.

Do not use water jet.

Combustible but not readily ignited. May form explosible dust clouds in air. Combustion or thermal decomposition will evolve toxic, irritant and flammable vapors. By analogy with similar materials, the product may decompose if heated to temperatures above 392°F

(200°C).

A self contained breathing apparatus and suitable protective clothing should be worn in fire

conditions.

6. ACCIDENTAL RELEASE MEASURES

Caution - spillages may be slippery.

Methods and materials for containment and cleaning up

Sweep up and shovel into waste drums or plastic bags. Wash the spillage area with water.

7. HANDLING AND STORAGE

HANDLING Product as supplied: Avoid contact with eyes. Avoid prolonged skin contact. Unlikely to

represent a dust hazard under normal handling conditions.

Process Hazards

The product may be suitable for a wide range of industrial

The product may be suitable for a wide range of industrial applications and therefore it is impossible to make detailed recommendations regarding all process hazards. The following constitutes general advice: Extra care should be taken to prevent burns from contact with hot material. Thermal processing requires adequate ventilation to remove any monomer decomposition products, and use of inert atmosphere may be required in some processes to safely decompose the resin when it is used as a binder. Any thermal processing must consider the time-temperature decomposition of the resin. All polymers degrade to some extent at their processing temperature, an effect which increases with increasing temperature. It is therefore impossible to be precise about which substances may be evolved. However, it is only the minor components which vary substantially. The major components are given in Section 10. If the product is to be used in applications for which the hazards are not fully understood it is recommended to consult the supplier before use.

STORAGE Acrylic polymers are supplied in either bags or bulk containers. Keep containers in a clean,

cool and dry area away from heat sources. Natural ventilation is adequate.

Storage temperature (°C): Ambient.
Incompatible materials: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Substance	CAS No.	OSHA PEL	ACGIH	ACGIH	Company Std.	Company
		TWA	TWA	STEL	TWA	Std.
						STEL
Particulates (Total dust)		15 mg/m³	Not			
(Respirable dust)		5 mg/m³	established.			
The following values apply to substances						
which may be evolved during thermal						
processing.						
Methyl methacrylate	80-62-6	100 ppm	50 ppm	100 ppm	50 ppm	100 ppm
		410 mg/m ³	(205 mg/m³)	(410 mg/m³)		
				(SEN;A4)		
n-Butyl methacrylate	97-88-1	Not	Not		50 ppm	100 ppm
		established.	established.			
Methacrylic acid	79-41-4	50 ppm	50 ppm			

Revision: GHS4

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection



Wear eye/face protection. Safety spectacles/goggles/full face shield.

Skin protection



Not normally required.

Respiratory protection



A suitable dust mask or dust respirator with filter type P3 or FFP3 (EN143 or EN149) may be appropriate. In the unlikely event of formation of particularly high levels of dust a self contained breathing apparatus may be appropriate.

Thermal hazards

Wear thermal insulating gloves when handling hot masses.

Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. A suitable mask with filter type A may be appropriate. In the unlikely event of formation of particularly high levels of vapor a self contained breathing apparatus may be appropriate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Beads.
Color White.

Odor Typically methacrylate.

pH (Value)

Boiling Point (°C)

Not available.

Not applicable.

Flash Point (°C) 300

Relative Evaporation Rate (Ether = 1) Not applicable. Flammable Limits Not applicable. Vapour pressure (Pascal) Not applicable. Vapor Density (Air=1) Not applicable. Specific Gravity 1.18 Solubility (Water) Negligible. Solubility (Other) Not available. Partition Coefficient (n-Octanol/water) Not applicable.

Viscosity (mPa. s)

Explosive Properties

Oxidizing properties

Not applicable.

Not applicable.

Not applicable.

Not applicable.

10. STABILITY AND REACTIVITY

Reactivity Non-reactive material.

Chemical stability Stable under normal conditions.

Hazardous Reactions None known.

Conditions to avoid Keep away from heat. Avoid dust generation.

Materials to avoid None known.

Hazardous decomposition product(s) Methyl methacrylate, n-Butyl methacrylate, Methacrylic acid, Carbon dioxide, Carbon

monoxide.

Revision: GHS4

ELVACITE® ACRYLIC RESIN - POLY(MMA/nBMA/MAA) BASED

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Ingestion Low oral toxicity.

Inhalation Unlikely to be hazardous by inhalation. High concentrations of vapour from hot operations

may be harmful, cause irritation of the respiratory tract and slight narcotic effects.

Skin corrosion/irritation Unlikely to cause skin irritation.

Serious eye damage/irritation Dust may cause irritation.

Skin sensitization data Contains: (Methyl methacrylate, n-Butyl methacrylate). During normal handling this will not

constitute a hazard. If the polymer matrix is destroyed e.g. when the product is dissolved in organic solvent, chemical residues will be released from the polymer matrix. Under these

conditions, they may produce an allergic reaction in persons already sensitised.

Chronic exposure This type of material has been in use for many years with no evidence of adverse effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity The product is predicted to have low toxicity to aquatic organisms.

Persistence and degradability The product is non-biodegradable in soil. There is no evidence of degradation in soil and

water.

Bioaccumulative potential The product has low potential for bioaccumulation.

Mobility The product is predicted to have low mobility in soil.

Other adverse effects None known.

13. DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Clean scrap may be reprocessed. Certain packages are returnable. Please consult your local office for further details. Ensure that all packaging is disposed of safely.

Disposal methods May be disposed of by landfill in accordance with local regulations. Incineration may be used

to recover energy value.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF Not Classified as Dangerous for Transport.

TRANSPORTATION)

UN No. Not applicable.
Proper Shipping Name Not applicable.
Class Not applicable.
Packing group Not applicable.
Environmental hazards Not applicable.
Special precautions for user Not applicable.
Transport in bulk according to Annex II of Not applicable.

MARPOL 73/78 and the IBC Code

15. REGULATORY INFORMATION

SARA 302 - Extremely Hazardous Not applicable.

Substances

SARA 313 - Toxic Chemicals None

US State Regulations

California SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS

OR OTHER REPRODUCTIVE HARM None known.

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER None

known.

16. OTHER INFORMATION

The following sections contain revisions or new 1, 3, 5, 7, 8, 9, 10, 11, 15

statements:

Date of preparation: 13 -July- 2016

Inventory Status

European Union To the best of our knowledge all chemicals in this product comply with REACH regulations.

United States (TSCA) Listed in TSCA Canada (DSL/NDSL) Listed in DSL Japan (ENCS) Listed in ENCS Philippines (PICCS) Listed in PICCS Australia (AICS) Listed in AICS Listed in KECI South Korea (KECI) Listed in IECSC China (IECSC) Taiwan (TCSI) Listed in TCSI New Zealand (NZIoC) Listed in NZIoC

Compliance with other Regulatory Chemical Inventories cannot be assumed, please contact supplier for further information.

LEGEND

Note: : Not all of the following are necessarily contained in this Safety Data Sheet:

LTEL: Long Term Exposure Limit STEL: Short Term Exposure Limit TWA: Time Weighted Average PEL: Permissible Exposure Levels

OSHA: Occupational Safety and Health Administration SARA: Superfund Amendments and Reauthorisation Act WHMIS: Worker Hazardous Materials Information System

ELVACITE® is the Registered Trade Mark of companies within the Mitsubishi Rayon Lucite Group Limited Group of companies.

MEDICAL USE: CAUTION: DO NOT USE IN MEDICAL APPLICATIONS INVOLVING IMPLANTATION IN THE HUMAN BODY. Lucite International Inc. has performed no clinical testing on the use of this product in any medical application. Lucite International Inc. has no data to support the use of this product in any medical application. This product was not designed or manufactured for use in implantation in the human body or in contact with internal body fluids or tissues. Lucite International Inc. has neither sought, nor received, approval from any regulatory agency for the use of this product in implantation in the human body or in contact with internal body fluids or tissues.

It is the responsibility of the end-product manufacturer to identify all market and use-specific regulations and to ensure compliance with these regulations.

Subject to the exclusions and limitations set out below the Information contained in this publication or as otherwise supplied to the User is believed to be accurate and has been given in good faith. It is for the User to use the Information contained in this publication or as otherwise supplied to the User with care and satisfy itself of the suitability of the product for their intended use and the applicability of the advice given. Except to the extent that exclusion is prevented by applicable law Lucite International Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded and accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Revision: GHS4