

Revised 2/13/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : FLOOR STRIPPER

Material number : 031

Manufacturer or supplier's details

Company : GETT

Address : 58-90 55th Street
Maspeth, NY 11378

Telephone : 877-277-6579

Emergency telephone numbers**For a Medical Emergency** : 800-424-9300**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Floor Care

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	liquid
Color	colorless, clear
Odor	solvent-like

GHS Classification

Skin corrosion : Category 1

Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Potassium Hydroxide	1310-58-3	≥ 10 - < 15
2-butoxyethanol	111-76-2	≥ 4 - < 10
Nonylphenol Polyethylene Glycol Ether	9016-45-9	$\geq .1$ - < 5

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
Remove to fresh air.

In case of skin contact	: Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
-------------------------	---

FLOOR STRIPPER

In case of eye contact	: Small amounts splashed into eyes can cause irreversible tissue damage and blindness. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain. Causes severe skin burns and eye damage. Review section 2 of SDS to see all potential hazards.
Notes to physician	: Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Dry chemical Water spray jet Alcohol-resistant foam Carbon dioxide (CO ₂)
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: Carbon dioxide (CO ₂) Carbon monoxide Smoke Nitrogen oxides (NO _x)
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	: Collect contaminated fire extinguishing water separately. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Standard procedure for chemical fires.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

FLOOR STRIPPER

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes, inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Provide sufficient air exchange and/or exhaust in work rooms.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Store and keep away from, oxidizing agents and acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm, 24 mg/m ³	NIOSH REL
		TWA	50 ppm, 240 mg/m ³	OSHA Z-1
		TWA	25 ppm, 120 mg/m ³	OSHA P0
		PEL	20 ppm, 97 mg/m ³	CAL PEL

FLOOR STRIPPER

Potassium hydroxide	1310-58-35	C	2 mg/m3	USA. ACGIH
Remarks	Eye, skin, and upper respiratory tract irritation.			
		C	2 mg/m3	USA. OSHA – Table Z-1 Limits for Air Contaminants – 1910.1000
		C	2 mg/m3	USA. NIOSH Recommended Exposure Limits

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

FLOOR STRIPPER**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Color	: colorless, clear
Odor	: solvent-like
Odor Threshold	: No data available
pH	: 13.55
Melting point/freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: > 93.3 °C Method: TCC
Evaporation rate	: < 1
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: 19 hPa (20 °C)
Relative vapor density	: No data available
Density	: 1 g/cm ³
Solubility(ies)	
Water solubility	: soluble in cold water, soluble in hot water
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous	: No decomposition if stored and applied as directed.

FLOOR STRIPPER

reactions	
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Acids Oxidizing agents
Hazardous decomposition products	: Carbon oxides Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include blistering, irritation, burns, and pain.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	Confirmed animal carcinogen with unknown relevance to humans 2-butoxyethanol 111-76-2
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity**Product:**

Acute oral toxicity	: Acute toxicity estimate : 4,262 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 45.84 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : 4,471 mg/kg Method: Calculation method

Components:**2-butoxyethanol:**

FLOOR STRIPPER

Acute oral toxicity : LD50 Oral Rat: 880 mg/kg
Acute dermal toxicity : LD50 Dermal Rabbit: 1,060 mg/kg

Potassium Hydroxide:

Acute oral toxicity : LD50 Oral Rat: 365 mg/kg
Primary Skin Irritation Rabbit, 24 hrs, severe
Primary Eye Irritation Rabbit, 24 hrs, severe

Nonylphenol Polyethylene Glycol Ether:

Acute oral toxicity : LD50 Oral Rat: 3,310 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product:**

Remarks: No data available

FLOOR STRIPPER**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Component:

	Aquatic Plants	Fish	Water Flea
2-butoxyethanol	EC50 1840 mg/l 72 hrs	LC50 1490 mg/l 96 hrs	No Data Available
Potassium Hydroxide	EC50 61 mg/l, 96 hrs	LC50 179 mg/l, 96 hrs	EC50 60 mg/l 48 hrs

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

SAFETY DATA SHEET

Waste from residues

: Dispose of in accordance with local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL
--

Transportation Regulation: IMDG (Vessel): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL
--

Transportation Regulation: IATA (Passenger Air): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL
--

Transportation Regulation: TDG (Canada): NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL
--

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

FLOOR STRIPPER

SECTION 15. REGULATORY INFORMATION

TSCA list : Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy
The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components of this product. See 79 FR 59186.
This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR).
This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D..

EPCRA - Emergency Planning and Community Right-to-Know Act**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
2-butoxyethanol 111-76-2 5%

FLOOR STRIPPER

FLOOR STRIPPER

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Danger:**

: Causes severe skin burns and eye damage.

:

Prevention: Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or

FLOOR STRIPPER

hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.