

# **Safety Data Sheet**

Copyright,2019,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 18-5746-5
 Version Number:
 8.05

 Issue Date:
 10/21/19
 Supercedes Date:
 05/22/19

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Novec<sup>TM</sup> 1720 Electronic Grade Coating

#### **Product Identification Numbers**

ID Number UPC ID Number UPC

98-0212-3193-5 0 00 51135 71627 4 98-0212-3238-8

98-0212-3694-2

7100003760, 7100064103, 7100064107

#### 1.2. Recommended use and restrictions on use

### Recommended use

For Industrial Use Only. Not Intended for Use as a Medical Device or Drug., Coating applications in electronic industry **Restrictions on use** 

3M Electronics Markets Materials Division (EMMD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMMD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** Electronics Materials Solutions Division **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

## 2.1. Hazard classification

10/21/19

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

### Signal word

Not applicable.

#### **Symbols**

Not applicable.

#### **Pictograms**

Not applicable.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	163702-07-6	20 - 80
METHYL NONAFLUOROISOBUTYL ETHER	163702-08-7	20 - 80
Fluorinated Silane	Trade Secret*	< 1

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

No need for first aid is anticipated.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

### **Hazardous Decomposition or By-Products**

\_\_\_\_

**Substance** 

Carbon monoxide Carbon dioxide Hydrogen Fluoride **Condition** 

During Combustion During Combustion During Combustion

#### 5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

#### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid release to the environment. No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from strong bases.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

tor the component.				
Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Butane, 1,1,1,2,2,3,3,4,4-	163702-07-	AIHA	TWA:750 ppm	
nonafluoro-4-methoxy-	6			
METHYL	163702-08-	AIHA	TWA:750 ppm	
NONAFLUOROISOBUTYL	7			
ETHER				

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

#### 3M<sup>TM</sup> Novec<sup>TM</sup> 1720 Electronic Grade Coating

10/21/19

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene

### Respiratory protection

#### During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

### Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state Liquid Color Colorless

Specific Physical Form:

Odor

Odor

Odor threshold

No Data Av

Odor thresholdNo Data AvailablepHNot ApplicableMelting point-135 °C

**Boiling Point**61 °C [@, 760 mmHg]

Flash Point No flash point

**Evaporation rate** 49 [*Ref Std*:BUOAC=1]

Flammability (solid, gas)

Flammable Limits(LEL)

None detected [

Flammable Limits(LEL)

None detected [Details: NONE acc to ASTM E681-94, @100C]

Flammable Limits(UEL)

None detected [Details: NONE acc to ASTM E681-94, @100C]

Vapor Pressure 202 mmHg [@ 25 °C]

Vapor Density

8.6 [Ref Std: AIR=1]

**Density** 1.5 g/ml

Specific Gravity

1.5 [Ref Std: WATER=1]

Solubility In Water< 12 ppm</th>Solubility- non-waterNo Data Available

Partition coefficient: n-octanol/ water No Data Available

**Autoignition temperature** 405 °C [Details:(ASTM E659-84)]

Decomposition temperature

No Data Available

Viscosity 0.6 centipoise [@ 23 °C ]

Molecular weightNo Data AvailableVolatile Organic Compounds[Details: Exempt]

Percent volatile > 99 % weight

VOC Less H2O & Exempt Solvents [Details: Exempt]

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Not determined

#### 10.5. Incompatible materials

Strong bases

## 10.6. Hazardous decomposition products

<b>Condition</b>
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat
At Elevated Temperatures - extreme conditions of
heat

10/21/19

Toxic Vapor, Gas, Particulate

At Elevated Temperatures - extreme conditions of

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

No known health effects.

### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

#### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

### **Ingestion:**

No known health effects.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
METHYL NONAFLUOROISOBUTYL ETHER	Dermal		LD50 estimated to be > 5,000 mg/kg
METHYL NONAFLUOROISOBUTYL ETHER	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
METHYL NONAFLUOROISOBUTYL ETHER	Ingestion	Rat	LD50 > 5,000 mg/kg
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Dermal		LD50 estimated to be > 5,000 mg/kg
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Ingestion	Rat	LD50 > 5,000 mg/kg
Fluorinated Silane	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value

\_\_\_\_

3M <sup>TM</sup> Novec <sup>TM</sup> 1720 Electronic	Grade Coating	10/21/19
--	---------------	----------

METHYL NONAFLUOROISOBUTYL ETHER	Rabbit	No significant irritation
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Rabbit	No significant irritation
Fluorinated Silane	Rabbit	No significant irritation

## Serious Eye Damage/Irritation

Name	Species	Value
METHYL NONAFLUOROISOBUTYL ETHER	Rabbit	No significant irritation
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Rabbit	No significant irritation
Fluorinated Silane	Rabbit	Mild irritant

### **Skin Sensitization**

Name	Species	Value
METHYL NONAFLUOROISOBUTYL ETHER	Guinea	Not classified
	pig	
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Germ Cell Mutagenicity**

Germ Cen Mutagementy	serm centraungement						
Name	Route	Value					
METHYL NONAFLUOROISOBUTYL ETHER	In Vitro	Not mutagenic					
METHYL NONAFLUOROISOBUTYL ETHER	In vivo	Not mutagenic					
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	In Vitro	Not mutagenic					
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	In vivo	Not mutagenic					
Fluorinated Silane	In Vitro	Not mutagenic					

## Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
METHYL NONAFLUOROISOBUTYL ETHER	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
METHYL NONAFLUOROISOBUTYL ETHER	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
METHYL NONAFLUOROISOBUTYL ETHER	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Butane, 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation

### Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL NONAFLUOROISOBUT YL ETHER	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
METHYL NONAFLUOROISOBUT	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913 mg/l	10 minutes

YL ETHER						
Butane, 1,1,1,2,2,3,3,4,4-	Inhalation	nervous system	Not classified	Dog	LOAEL 913	10 minutes
nonafluoro-4-methoxy-					mg/l	
Butane, 1,1,1,2,2,3,3,4,4-	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913	10 minutes
nonafluoro-4-methoxy-					mg/l	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL NONAFLUOROISOBUT YL ETHER	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
METHYL NONAFLUOROISOBUT YL ETHER	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
METHYL NONAFLUOROISOBUT YL ETHER	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
METHYL NONAFLUOROISOBUT YL ETHER	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Butane, 1,1,1,2,2,3,3,4,4- nonafluoro-4-methoxy-	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Butane, 1,1,1,2,2,3,3,4,4- nonafluoro-4-methoxy-	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Butane, 1,1,1,2,2,3,3,4,4- nonafluoro-4-methoxy-	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Butane, 1,1,1,2,2,3,3,4,4- nonafluoro-4-methoxy-	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

\_\_\_\_

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

# **SECTION 15: Regulatory information**

#### 15.1. US Federal Regulations

Contact 3M for more information.

## **EPCRA 311/312 Hazard Classifications:**

Physical Hazards

Not applicable

### Health Hazards

Not applicable

### 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required

10/21/19

components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: Other information**

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride and Perfluoroisobutylene (PFIB). During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

**HMIS Hazard Classification** 

**Health:** 0 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

 Document Group:
 18-5746-5
 Version Number:
 8.05

 Issue Date:
 10/21/19
 Supercedes Date:
 05/22/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com